

LASERGUIDE PROJECTORS

LASERGUIDE projectors have incorporated the latest advancements in laser, galvanometers, optics, temperature stabilization, and computing capabilities. Each of these technologies has improved individually, and when they are integrated into projectors, a systemic improvement of even greater proportion occurs.



PERFORMANCE

- Easiest to use
- Lowest cycle times
- Most reliable
- Lowest cost in use
- Made in USA

SPECIFICATIONS

Size:	13" x 10" x 7" / 33 x 25 x 18 cm
Weight:	18 lb/ 8 kg
Mounting Yoke:	2 lb/ 1 kg
Projection Angle:	60° (+/- 30°)
Projection Range:	Standard: 3' – 20' / 1m – 6m
Long Throw (LT) Option:	3' – 40' / 1m – 12m
Long Throw Extended (LTE) Option:	3' – 50' / 1m – 15m
Accuracy:	0.015"/0.38mm (meets Boeing D6-55902 requirements)
Beam Color:	Green (532nm)
Laser Line Width:	0.020"-0.075"/0.5mm-2mm
Laser Class:	CDRH Class II/IEC Class 2
Power Requirements:	110-240 VAC 50/60Hz
Set-Up Requirements (Interchangeability):	Plug and Play (no programming required)
Multitasking Capabilities:	4 simultaneous projections
Tool Location Requirements:	none (can be placed in any orientation)
Advanced Focus:	adjustable from computer
Warranty:	Two Years
Customer Support:	Unlimited free phone and email support for the life of the projector